



EASY PATCH

Concrete Repair Mortar

PRODUCT DESCRIPTION

Easy Patch is a one component, polymer-modified, high-performance repair and resurfacing mortar. **Easy Patch** is simply mixed with water and applied to concrete substrates from feather-edge to 1.50" thick in one application. Apply horizontally, vertically, or overhead. Apply with a trowel, brush or broom. The product sets in 20 to 30 minutes and is ready for foot traffic in 3 to 4 hours at 70° F. **Easy Patch** is a special blend of cement, aggregate and exclusive modifiers. Designed for general-purpose and high-performance concrete repair or resurfacing applications. Its high-strength composition provides long-lasting performance, making it ideal for both DIY enthusiasts and contractors.

TECHNICAL INFORMATION

- + Coverage.....50 Sq. Ft. @ 1/8" Thick
- + Color.....Concrete Gray
- + Freeze/Thaw Durability Rating.....Excellent
- + Working Time.....Approx. 10 Minutes
- + Packaging.....50 lbs. Bag

RECOMMENDED APPLICATIONS

- + Concrete Repair Up To 1.50" Thick
- + Smoothing and Filling Depressions
- + Underlayment For Tile and Carpet
- + Driveways, Sidewalks, and Patios
- + Interior or Exterior Applications



QUICK FACTS

- + Just Add Water
- + Portland Cement Based
- + Polymer Modified
- + High-Strength
- + Fast Setting
- + Interior or Exterior
- + Made In The USA



EASY PATCH

Concrete Repair Mortar

INSTRUCTIONS FOR USE

SURFACE PREPARATION

Surface preparation is critical to achieve long-lasting results. Existing concrete surfaces must be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign substance. Preparing the surface by mechanical means, such as grinding or shot blasting, is recommended. Prime all surfaces with Sure Bond before application.

MIXING

A heavy-duty drill and mixing paddle is required for proper mixing. Always add the dry powder to the water. It is recommended that you rinse out your mixing container with water before mixing the first batch. Start by adding 3.5–4 quarts of water in a suitable container. Slowly add 1 bag of Easy Patch and mix thoroughly for 2 minutes. Scrape the sides of the mixing bucket and continue to mix. Allow material to false set for one minute and re-mix. The exact amount of water needed may vary depending on the desired consistency. Do not exceed 4 quarts of water when mixing. Always introduce dry powder slowly to reduce lumping and ensure consistency. It is not recommended to mix more Easy Patch than you can use within 10 minutes. If mixing less than a full bag, mix 4 parts Easy Patch powder to 1 part water.

APPLICATION

Rub or scratch part of the mixed material onto the surface just prior to application. Do not allow rub or scratch coat to dry before applying the rest of the material. Use a trowel, brush, or broom to apply the Easy Patch. Do not re-temper already mixed material. Avoid applications in high winds, excessive heat, or blowing air directly on freshly placed products. The product will be set in 20 to 30 minutes. Allow 3 to 4 hours for foot traffic on horizontal repairs. For smoother finishes, mist with finishing aid while troweling.

SEALING/CURING

Easy Patch is self-curing and may be sealed with any of Deco-Crete's Cure and Seal products. For best results, wait a minimum of 24 hours before applying any sealer.

PRO TIPS

- + Add 3/4 of the bag and mix for 30-60 seconds, then add the remainder of the bag.
- + Do not mix more product than you can use within 10 minutes.
- + Pre-wet the mixing container before the first batch.
- + Mist with finishing aid for a smoother finish.



For tutorials and even more decorative concrete content, check out our YouTube channel by scanning the QR code, or check out our other social media accounts listed here.

